

PATENT
021857.000007

APPLICATION FOR UNITED STATES LETTERS PATENT

for

MODELESS EVENT-DRIVEN DATA TRANSFORMATION

by


**Paul C. Dingman,
Kathryn Van Dyken,
William G. Bunton and
Tom Landrum**

EXPRESS MAIL MAILING LABEL

NUMBER EL551406627US

DATE OF DEPOSIT October 10, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service
"EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 C.F.R. 1.10 on the date
indicated above and is addressed to: Assistant Commissioner for Patents, Washington D.C. 20231.



Signature

1 system; or to integrate the organization's systems with those of customers and suppliers
2 across the value chain. To be successful, an organization must transform data into
3 useable formats for internal departments, partners, and customers.

4 To make data available and meaningful for different recipients, data
5 transformation is often necessary. Data transformation generally refers to a sequence of
6 operations that transforms a set of input data into a set of output data. Though the term
7 data conversion has a slightly different technical connotation, it is often used
8 synonymously with the term data transformation. Data transformation allows for the
9 changing of the content, format, or data structure. Common content changes include
10 adding, deleting, aggregating, concatenating, and otherwise modifying existing data.
11 Common data formats include binary files, sequential files, embedded binary data,
12 EBCDIC data from mainframes, common file types created by C, COBOL, FORTRAN,
13 Basic, RPG, Pascal, and other languages, arrays, ISAMs and other record managers, PC-
14 based databases, accounting applications, and Web-based data reachable through
15 SQL/ODBC. Common data source structures may include spreadsheets, contact
16 managers, mail list software, and statistical packages.

17 The process of converting data becomes increasingly complicated with each
18 increase in the number of input data sources, the number of output data sources, the
19 content of the data sources, the format of the data sources, and the complexity of data
20 structures. For example, different data storage systems use data structures with different
21 structures. For example, mainframe systems typically use a hierarchical data storage
22 method, whereas client-server systems often use a relational database storage method.

23 *Handwritten: not* Current data transformation techniques are generally expensive to implement, are
24 not portable, and difficult to adapt to new or changing circumstances. For example,
25 point-to-point links are generally hand-coded customized data transformation programs.
26 Customized code is typically written in-house and is specific to a single application or
27 DBMS environment. On the positive side, such solutions generally provide exactly what
28 is needed and no more, and address requirements for which there may be no off-the-shelf
29 products. In-house development, testing and debugging also narrows the focus, and tends
30 to produce a workable, if non-versatile, solution. On the other hand, because these
31 routines are usually specific to a particular source or target database, they are difficult to

A

CONFIDENTIAL

1 port to other environments. These routines may also be difficult to repeat because the
2 routines are generally unique to each situation and because there is typically no
3 infrastructure in place to manage the processes. Finally, building custom routines robs
4 in-house DBAs of time better spent on other tasks. In addition, custom coded solutions
5 require continued maintenance because they must be modified every time a new
6 requirement is added to the system. Further, custom code may take a relatively long time
7 to implement with some legacy migration projects tying up critical IT staff for weeks,
8 month and even years.

9 Consultants and customized tools are also used by organizations with increasing
10 frequency today. Outside consultants typically have acquired extensive experience in
11 building data models, designing movement and transformation methodologies and
12 developing transformation tools. Such tools tend to be more portable, since they have
13 been developed with multi-platform DBMS environments in mind. Because database
14 consultants have had to become knowledgeable about business operations as well, these
15 tools also tend to address business processes adequately. However, all application
16 expertise leaves along with the consultant. In addition, because these routines are specific
17 to single aspects of the business, they are difficult to recreate for other branches or
18 divisions.

19 A common alternative to point-to-point links involves streaming data through a
20 conduit into a universal structure, transforming the data in a central hub, then streaming
21 the data through another conduit to the target format. Transforming the data may happen
22 in real time but requires downloading the structure into memory to make it possible to
23 apply a consistent set of visually defined transformation capabilities to an intermediate
24 data stream regardless of the data's original format or transformed format. This method
25 generally requires less programming code than point-to-point links. However, the
26 architecture tends to limit transformation operations, and less efficient versions increase
27 latency and complicate scalability. Further, loading the entire source structure into
28 memory may become prohibitive with large and complex structures.

29 The use of an iterative method addresses this last concern. Iterative data
30 transformation methods do not require the use of large amounts of memory that loading
31 the entire structure requires, because source data is examined one record at a time.

1 However, with current iterative methods, it is difficult to keep track of the relationship
2 between records.

3 Another relatively new technology, XML, has lured application developers with
4 the promise of an easier way to integrate data between applications and between
5 organizations over the Internet. However, as organizations rush to adopt progressive e-
6 business infrastructures such as XML to gain an edge over the competition, they are
7 stumbling upon an unsettling reality. Since the W3C released the public specifications
8 for XML in 1998, vertical industries and major corporations have already implemented
9 hundreds of disparate XML “standards.” Thus, a big hurdle for trading partners,
10 developers, and net market makers that need to interface with multiple production
11 systems and organizations is the wide range of XML standards (as well as other data
12 formats) that they will likely encounter.

13 Data transformation tools currently in use are generally expensive, time-
14 consuming to implement, programming-intensive, and inflexible. An ideal data
15 transformation tool requires a minimum amount of custom programming, has the
16 flexibility to work with varied data formats, contents, and structures, and possesses the
17 capability to adapt to different sources and targets.

18 GLOSSARY

19 The following illustrative explanations are provided to facilitate understanding of
20 certain terms used frequently herein, particularly in the Description of Illustrative
21 Embodiments. The explanations are provided as a convenience and are not limitative of
22 the invention.

23 **column** – the container for a single item of information in a row. Also known as
24 *field*.

25 **database** – one or more structured sets of persistent data, usually associated with
26 software to update and query the data. A simple database might be a single file
27 containing many records, each of which contains the same set of fields where each field
28 is a certain fixed width.
29

1 **Data Definition Language (DDL)** – those text commands that define, as opposed
2 to manipulate, data. For example, the SQL statements **CREATE TABLE**, **CREATE**
3 **INDEX**, **GRANT**, and **REVOKE**.

4 **Data Manipulation Language (DML)** – those text commands that manipulate,
5 as opposed to define, data. For example, the SQL statements **INSERT**, **UPDATE**,
6 **DELETE**, and **SELECT**.

7 **database management system (DBMS)** – a software system for managing
8 databases. These systems typically provide mechanisms for creating databases, defining
9 objects in the database (tables, views, *etc.*), manipulating data (inserts, updates, queries),
10 and controlling access to data (security).

11 **electronic data interchange (“EDI”)** – in common usage, generally refers to
12 either the ANSI standard (X12) or the ISO EDIFACT (Electronic Data Interchange for
13 Administration Commerce and Transport) standard formats.

14 **event** – an occurrence of significance to a particular task.

15 **field** – sometimes defined as the smallest addressable piece of a record, for both
16 defining record layouts or structures and for access data in a data record.

17 **file** – a named collection of data which is stored or processed as a single logical
18 unit. Files are generally subdivided into one or more types of *records*, which are
19 themselves subdivided into *fields*. *See also* field, and records.

20 **file layout** – the organization of the data within a *file*. Describes the types of
21 *records* used in the *file*. *See also* file, and records.

22 **fixed-length data type** – a data type that is always stored in the same number of
23 bytes, such as a two-byte integer. *See also* variable-length data type.

24 **foreign key** – a column or columns in a table that match the primary key in
25 another table.

26 **key** – a column or columns whose values identify a row.

27 **HDS** – HDS is a file-based hierarchical data system designed for the storage of a
28 wide variety of information. It is particularly suited to the storage of large multi-
29 dimensional arrays (with their ancillary data) where efficient access is needed. HDS
30 organizes data into hierarchies, broadly similar to the directory structure of a hierarchical
31 filing system, but contained within a single HDS container file. The structures stored in

and/or by the application that processes it. Typically, records can be of fixed-length or variable length with the length information contained within the record.

relational database – a database based on the relational model developed by E.F. Codd. A relational database allows the definition of data structures, storage and retrieval operations, and integrity constraints. In such a database, the data and relations between them are organized in tables. A table is a collection of records and each record in a table contains the same fields. Certain fields may be designed as keys, which means that searches for specific values of that field will use indexing to speed them up. Records in different tables may be linked if they have the same value in one particular field in each table.

row – a set of related columns that describe a specific entity. Also known as a *record*.

SAP Intermediate business Document ("IDOC") – an interchange format based on EDI used by SAP AG applications such as SAP R/3.

schema – a database object that contains one or more tables, often created by a single user.

session – an OLE DB object that serves as the context for a transaction.

Standard Generalized Markup Language ("SGML") – an information management standard adopted by the International Organization for Standardization ("ISO"), as ISO 8879:1986, as a means for providing platform-independent and application-independent documents that retain content, indexing, and linked information. SGML provides a grammar-like mechanism for users to define the structure of their documents and the tags they will use to denote the structure in individual documents. A complete description of SGML is provided in Goldfarb, C. F., *The SGML Handbook*, Oxford University Press, Oxford, 1990, and McGrath, S., *Parseme.1st: SGML for Software Developers*, Prentice Hall PTR, New Jersey, 1998, which are incorporated herein by reference.

standard query language (SQL) – a language which provides a user interface to relational database management systems, developed by IBM in the 1970s for use in System R. SQL is the de facto standard, as well as being an ISO and ANSI standard. It is often embedded in other programming languages.

SUMMARY OF THE INVENTION

In one broad respect, the present invention is directed to a system for data transformation comprising one or more read spokes with each read spoke configured to connect to one or more data sources, each data source having one or more data structures referred to collectively as source structures; one or more modeless write spokes with each modeless write spoke configured to connect to one or more data targets, each data target having one or more data structures referred to collectively as target structures; and a transformation engine operatively coupled to the one or more read spokes for retrieving data from the one or more data sources, and coupled to the one or more modeless write spokes for storing data in the one or more data targets, with the transformation engine comprising a transformation map that comprises one or more mappings that relates one or more source structures to one or more target structures and an event list comprising one or more event actions, each with a corresponding triggering event, and the transformation engine is configured to iterate through the data sources and detect occurrences of triggering events and execute the respective one or more event actions from the event action list in response to the detection of a triggering event. In a narrow respect, the transformation engine further comprises a query language preprocessor operable to review the data transformation map and evaluate embedded expressions in the one or more mappings. In another narrow respect, at least one of the event actions (called a "transformation event action") comprises retrieving at least source structure from the data source, transforming data from at least one source structure (called "transformed source data"), and storing the transformed source data into one or more target structures, with the transformation engine operable, in response to a transformation event action, to transform data specified by the transformation event action in a manner described by the data transformation map. In another narrow respect, a user interface is configured to allow a user to define the one or more data sources, and to define data structures in each of the one or more source databases. In another respect, a user interface is configured to allow a user to define the one or more data targets, and to define data structures in each of the one or more target databases. In yet another respect, a user interface is configured to allow a user to define the relationship between one or more data sources and one or more data targets. In a narrower respect, the user interface allows the user to relate source data

1 structures to target data structures. In particular, the user interface comprises a display
2 configured to graphically depict the relation between the source structures and the target
3 structures specified in the transformation map. In another narrower respect, the user
4 interface is configured to define the relationship between one or more data sources and
5 one or more data targets as a logical expression and/or as a numeric expression. In
6 another narrow respect, the transformation engine includes a display configured to show
7 the contents of the data source and the contents of the data structure. In other respects,
8 the triggering event is a generic source event, a generic target event, a generic
9 transformation event, or a specific source record event. In yet another narrow respect, the
10 transformation engine may also be configured to filter the data retrieved from the data
11 source, referred to as filtered source data, and can be further configured to iterate only
12 through the filtered source data. In narrower respects, the transformation engine filters the
13 data using predetermined sampling parameters governing a range or sample, or using
14 predetermined logical extraction criteria. In yet other respects, the read spokes connect to
15 the one or more data sources by utilizing a raw sequential mode such that an intuitive
16 visual parser reconstructs record layouts, or by utilizing a compatible physical file format
17 allowing the transformation engine to physically read from the data sources using the
18 native internal storage format.

19
20
21

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a high-level block diagram of a data transformation system according to an embodiment of the present invention.

FIG. 2 is a detailed object oriented block diagram of a data transformation system according to an embodiment of the present invention.

FIG. 3 is a block diagram of a transformation object model according to an embodiment of the present invention.

FIG. 4 is a flow chart of a data transformation method according to an embodiment of the present invention.

FIG. 5 is a flow chart depicting the transformation process according to an embodiment of the present invention.

FIG. 6 is a flow chart depicting the process used to initialize a transformation for execution according to one embodiment of the present invention.

FIG. 7 is a flow chart depicting one portion of the transformation loop process according to one embodiment of the present invention.

FIG. 8 is a flow chart depicting the other portion of the transformation loop process according to one embodiment of the present invention.

DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

The present invention addresses the shortcomings of the prior art with an event-driven transformation engine. As used in the present invention, the term "a" is used to mean "one or more."

The typical prior art technique used by many of the data transformation and data-loading utilities is a three step process that includes reading a record, evaluating a mapping to move the source field data to the target fields, and writing the record to the target. This process is repeated for each record in the data source, defining a very static process whereby one expects one target record to be written for each source record. Applications requiring updates to multiple targets would require multiple passes over the source data and in some cases would involve staging the data to intermediate data stores.

The event-driven system and method of the present invention is more flexible and can be easily customized to fit the needs of a given situation. In particular, the present

invention allows for the simultaneously updating of multiple target databases with a single pass of the data source. The present invention handles event actions in a flexible manner, allowing, for example, each of the multiple targets to get the exact same data (*i.e.*, a single mapping and multiple writes) or each target to receive data in a customized manner (*i.e.*, multiple maps and writes). This functionality has applications for data synchronization and replication in addition to traditional data transformation applications.

Further, the traditional technique is generally limited to applications where the source data is homogenous. Multiple record types could be handled using filtering but would require making multiple passes over the source data. A drawback to this approach is that converting the data in a piecewise, multi-pass fashion makes it hard if not impossible to maintain relationships between the different record types.

Systems of the present invention allow for heterogeneous data manipulation operations on multiple objects in a database management system. For example, a transformation can be set up so that different kinds of data will trigger different events. The event processing can handle hierarchical data, data with mixed record types, sequential report data (data with header, detail, and trailer records). Further, the use of events make it easy to aggregate data, route data to different kinds of targets, or to change the structure of the data on multiple levels. Still further, in some embodiments of the present invention, the heterogeneous data manipulation on multiple objects in the DBMS may be done in a single transformation pass.

FIG. 1 illustrates a transformation system **100** according to one embodiment of the present invention. As shown, transformation system **100** employs a modular hub and spoke architecture. A hub and spoke architecture is well-suited for data transformation because it permits infinite extensibility, both in the power of the central transformation engine, as well as the richness of formats supported by the spokes. Though a hub and spoke architecture is used with the claimed system of the present invention, the present invention contemplates the use of other architectures with the claimed method without departing from the scope of the invention.

The hub is a data transformation engine **110**, which functions generally to read and transform various types of structured data. Read spokes **120** and write spokes **130** are operatively coupled to transformation engine **110**, serving as the interface between

1 transformation engine **110** and data sources **124** and data targets **134**, respectively. As
 2 used in the present invention, a spoke is a data access adapter for one or more specific
 3 types of data. The spoke objects provide the necessary information to allow
 4 transformation engine **110** to retrieve and write data to the data structures in a source or
 5 target. The specific information that a spoke requires depends on the type of data and the
 6 data structure. Preferably, transformation system **100** has preprogrammed spokes for
 7 many of the common data formats and DMBSs, including, but not limited to, Oracle,
 8 IBM DB2, Microsoft SQL Server, dBase, XML, delimited ASCII, and fixed ASCII. In
 9 addition, spokes may also be implemented for providing access to data through various
 10 middleware products such as OLE DB and ODBC, and through a variety of application
 11 programming interfaces such as Remedy ARS. It is noted that the present invention is
 12 not limited to the use of any one or set of specific data types. Spokes can be developed
 13 for any data type and structure, thereby allowing transformation engine **110** to interface
 14 with any data type and structure.

15 In many applications, data sources **124** and data targets **134** may be databases
 16 having objects, with records and fields. However, the present invention is compatible
 17 with any store of data, that incorporate any type of data structures, including without
 18 limitation data stored in random access memory, data in a data stream, a result of a query
 19 against a DBMS, an electronic message, and an application programming interface.

20 Preferably, transformation engine **110** operates in real-time, meaning that it is
 21 capable of connecting to and passing records to and from sources **124** and targets **134**
 22 without using an intermediate file. Thus, while data passes through the transformation
 23 engine **110**, it can be massaged on the fly into the exact output format required. The
 24 types of transformation performed by transformation engine **110** are not limited by the
 25 present invention, and are discussed below in detail.

26 In one embodiment, transformation system **100** may be written in C++. In
 27 particular, the elements (transformation engine **110** and read spokes **120** and write spokes
 28 **130**) may be C++ code wrapped as Windows DLLs and COM components.
 29 Consequently, transformation system **100** may be a portable, cross-platform, expandable
 30 data transformation solution that may be incorporated into complementary products.

1 **FIG. 2** is an object-oriented block diagram of a more detailed transformation
2 system **200** according to an embodiment of the present invention. As shown,
3 transformation system **200** may include a map designer **210**, a transformation map
4 repository **214**, transformation engine **110**, source spokes **120** and target spokes **130**.

5 *Inst 2* Map designer **210** provides an interface that permits user **10** to specify the
6 relationships between data (called "mappings") retrieved from source **124** and written to
7 target **134**. In some embodiments, this interface may allow the mappings to be
8 established graphically. In other embodiments, the mappings may be specified as a set
9 one or more expressions or rules. In yet other embodiments, a default set of mappings
10 may be used in the absence of the user input. In one particular embodiment, the default
11 mapping is a one-to-one mapping between the source **124** and the target **134**.

12 As illustrated, mappings may be stored in and loaded from transformation map
13 repository **214**. Though transformation map repository **214** is depicted, its inclusion with
14 the present invention is optional. When included, however, it allows user **10** to reuse,
15 adapt, and/or improve upon previously specified mappings.

16 In many instances, information about data source **124** and data target **134** can be
17 drawn from an external repository or database catalog, copied from a previously executed
18 data flow, or defined interactively. Underlying such functionality is metadata, which in
19 its broad definition is data about data that informs users how data arrived in the data
20 store, how the data is laid out, where it came from, and/or how it was transformed. In the
21 illustrative embodiment, map designer **210** provides user **10** with metadata about data
22 source **124** and data target **134**, retrieved by their respective spokes **120** and **130**. In one
23 particular embodiment, map designer **210** integrates and blends the metadata into the
24 design interface, allowing user **10** to make use of it when specifying the mapping.
25 Further, metadata may also be generated and stored with each transformation map stored
26 in transformation map repository **214**. The information provided by metadata varies
27 depending on its origin and the object that it describes. However, in this type of
28 application, metadata may typically include, without limitation, the specifications of a
29 transformation; the data structures of data source **124** and data target **134**; and
30 information regarding system changes and the accomplishment of transformation goals.

For 3

When a transformation is executed, transformation engine 110 retrieves the applicable transformation rules from either from the map designer or the transformation map repository. Transformation engine 110 then directs source spoke 120 to retrieve the applicable data from source 124. Transformation engine 110 performs the necessary functions and actions on the data and then send the data to target spoke 130 to be stored in target 134, as specified by the transformation rules in the transformation map.

In some embodiments (not shown), the transformation system 200 may also include a real-time source/target monitor that displays the contents of both source 124 and target 134. Advantageously, user 10 could monitor the display to ensure that the transformation is correct.

FIG. 3 is a high-level object model diagram for the objects that participate as part of the design and execution of a transformation according to one embodiment of the present invention.

Transformation object 300 is the root object of the object model. It is responsible for associating a TransformationMap 310 with transformation runtime metadata including transformation execution options, source and target connection information, and source and target record selection criteria. It is also responsible for the loading and execution of transformation maps 310.

Action object 352 is an individual instruction (also called an event action) used in response to a transformation event or an error event during the execution of a transformation. Actions collection 350 is an ordered collection of action objects 352. Each event handler 342 routine consists of an action collection 350.

For 4

ConnectionInfo objects 322 and 332 manage information used to connect to data source 124 and data target 134, respectively. ConnectionInfo objects 322 and 332 may be used by source spoke 120 and target spoke 130 to provide access to source object 124 and target object 134, respectively. For simple filed-based data sources, this may just be the name of the file (local or remote file system or a URI). For database management systems, this information could most often include the name of the DBMS server, the name of the database, a user ID, a password, and a reference to the DBMS object (table name or a query result). The connection information may also include option settings to control the behavior of the spoke used for the data access.

1 Spoke objects **120** and **130** are responsible for providing access to the source or
2 target data and metadata. Source spoke **120** is configured to read records and evaluate
3 record recognition rules to determine record types. Target spoke **130** is responsible for
4 updating data target **134** with the transformation results (insert, update, or delete). Both
5 source and target spokes **120** and **130** may also provide information about their
6 capabilities and requirements. This information is used to assist in the design of
7 transformation maps and connection information.

8 TransformationMap **310** is the root object for the transformation metadata. It is
9 responsible for managing the rules and metadata used for executing a transformation.

10 *Inst A5* EventHandler object **342** manages a collection of actions **350** used to handle a
11 specific type of event. EventHandler object **342** is also responsible for compiling and
12 executing actions **350**. EventHandlers **340** is an array of EventHandler **342** objects. In
13 one embodiment, five types of EventHandlers **340** are used to handle processing of
14 transformation **300**, source **324**, target **334**, source record layout, and target record layout
15 events.

16 *Inst A6* Generally, the Actions **350** defined in the EventHandlers **340** are used to direct
17 operations in the transformation engine. Permissible Actions **350** may be dictated several
18 factors, including the capabilities of the transformation engine, and the type of target
19 spoke or adaptor that is used. In some embodiments, a “modal” target adaptor is used. In
20 these embodiments, the type of operation performed by the target adaptor is implied by
21 the current output mode. As described below in more detail, the output mode may be
22 specified when defining the target. Examples of output modes include, without
23 limitation: **Replace File/Table** – create a new data target or table, OR overwrite both
24 the data and the structure of an existing file or table; **Append to File/Table** – keep the
25 existing records and add new records to an existing file or table, OR add records to an
26 empty table; **Update File/Table** – searches an existing data target for a match in the key
27 fields, which the user defines in target keys/indexes, and updates data in the specified
28 manner; **Clear File/Table contents and Append** – preserves the target record layout and
29 the relationships between tables (if the user has defined them) and discards any existing
30 records; **Delete from File/Table** – searches an existing data target for a match in the key
31 fields, which the user has defines in target keys/indexes, and deletes data in the specified

1 manner. In some embodiments of the present invention, event actions that may be used
2 with modal target adaptors include, without limitation:

- 3 • **Abort** – used to abort the execution of the execution
- 4 • **Resume** – used within an error event handler to resume execution of an
5 action list which was interrupted by an exception
- 6 • **Clear** – used to clear the values for a target record layout
- 7 • **Map** – execute the mapping expressions for a target record layout
- 8 • **Put** – write a record to a target
- 9 • **ClearMapPut** – a composition action combining the clear, map, and put
10 actions
- 11 • **Execute** – used to execute expression language code
- 12 • **LogMessage** – used to write a message to the transformation log file
- 13 • **LogTargetRecord** – used to display the contents of a target record in the
14 transformation log
- 15 • **ClearInitialize** – used to initialize a target record with default values

16 It is noted that these event actions may perform different functions depending on the
17 active output mode. For example, in a **Replace File/Table** output mode, the **Put**
18 command would essentially erase an existing record in the target and write a new record
19 in its place. In contrast, during a **Append to File/Table** output mode, the **Put** command
20 would append a new record to the target. In these embodiments, the specification of the
21 target object and the operation on that object may be specified by the target adaptor.

22 In other embodiments, the specification of the target object and the operation on
23 an object may be specified in the Actions 350 used in the event handlers for the
24 transformation engine. Accordingly, the target spoke or adaptor performs independent of
25 the output mode, hereinafter referred to as a modeless spoke or adaptor. Advantageously,
26 the output more may be more dynamic because the specification of the object and data
27 operation is deferred to the point where an event handler executes an output action. For
28 example, in embodiments with modeless target adaptors, any sequence of data
29 manipulation operations over any set of target objects may be performed within a single
30 step transformation, rather than one output mode at a time. Further, the same record
31 layout may be used to output to multiple objects. Similarly, it is also possible to define

multiple record layouts for use with a single target object. Each record layout can have different mapping expressions and represent different views of the target object. Sharing a record layout between multiple objects can reduce the complexity of a map and using multiple record layouts per object provides greater flexibility in expressing transformation rules. In one particular embodiment, the modeless target adaptors for SQL databases can be configured to write the generated query statements to a script file and/or to execute the query statements as they are generated.

Examples of Actions 350 that may be used with modeless target adaptors may include, but are not limited to:

- **Insert Record** – inserts the data from the target record memory buffer into a named object. The target adaptor instance, the target object, and the target record type may be specified using three input parameters such as the target adaptor instance, the target object, and the target record type.
- **Update Record** – uses the data in the target record memory buffer to modify records in the named object. The target adaptor instance, the target object, and the target record type may be specified using three input parameters.
- **Delete Record** – uses the data in the target record memory buffer to select records in the named object for deletion. The target adaptor instance, the target object, and the target record type may be specified using three input parameters.
- **Drop Table** – drop a table. The target adaptor instance and the target object may be identified with the input parameters.
- **Create Table** – create a table. The target adaptor instance, the target object, and target record type may be identified with the input parameters.
- **Create Index** – create an index. The target adaptor instance, the target object, the target record type, and uniqueness flag may be specified with the input parameters.
- **SQL Statement** – execute a query language statement. The statement may include embedded expressions from the integration language provided by the transformation engine.

- **SQL File** – execute a query language statement loaded from file. The statement may include embedded expressions from the integration language provided by the transformation engine.
- **MapInsert Record** – executes mapping expressions and inserts the resultant values from the target record memory buffer into a named object. The target adaptor instance, the target object, and the target record type may be specified using three input parameters.
- **ClearMapInsert Record** – clears the target record memory buffer, executes mapping expressions, and inserts the resultant values from the target record memory buffer into a named object. The target adaptor instance, the target object, and the target record type may be specified using three input parameters.

Field object **366** manages the data and metadata for a single field in a record layout. This may include information about the data type of the field, default value, key markers, documentation, and mapping expressions. Fields object **346** is an ordered collection of Field objects **366**, whereby the collection may be used to define a record layout.

MapExpression **368** may be a piece of code used to derive the value for a specific field in a target record. MapExpression **368** may be used to compile, syntax check, and evaluate the code when the **Map** action is executed.

RecordLayout object **362** is a named collection of Fields **346**. It provides support for storing record layout metadata (name, description, *etc.*) and provides operations for managing the collections of fields at design time and for evaluating mapping expressions during transformation run time. RecordLayouts object **360** is used to manage the collection of records layouts for source **324** or target object **334**. RecordLayouts object **360** may also serve to associate the record layouts with the rules used to recognize the records.

RecordRecognitionRule object **372** may be used to define an association between a specific record layout and a logical condition. RecordRecognitionRules **370** object is the collection of RecordRecognitionRule objects **372**.

1 Source object 324 manages the metadata for a transformation source and provides
2 indirect access to the source data object through a source spoke 120. Sources object 320
3 is the collection of Source objects 324 used for a transformation map.

4 Similarly, the Target object 334 manages the metadata for a transformation target
5 and provides indirect access to the target data object through a target spoke 130. The
6 Targets object 330 is the collection of Target objects 334 used for a transformation map.

7 **FIG. 4** is a high level flow chart that depicts the basic process for data
8 transformation according to one embodiment of the present invention. Generally, in the
9 illustrative embodiment, the order of steps 400, 410, 420, and 430 is generally not
10 relevant. As shown, to perform a data transformation, a source must be defined 400, a
11 target must defined 410, a transformation map must be defined 420, event actions must
12 be specified 430, and then the actual data transformation 500 is executed (described in
13 detail in conjunction with **FIGs. 5-8**).

14 **Defining the source**

15 Defining the source 400 provides the transformation engine 110 with the
16 information to retrieve data from the data structures in the data source. The specific
17 parameters that must be supplied to define a particular source varies on several factors
18 including, without limitation, the type of data structures used in the source, the presence
19 of a file sniffer, and whether the source is of a commonly used type.

20 First, the location(s) of the data source(s) must be specified. In many cases the
21 data source may be a file stored on the user's computer or at a remote location (*e.g.*, on a
22 network). In other instances, however, the data source may be a data stream in which
23 case the data stream must be identified, *e.g.*, by name or memory location.

24 After the data source is located, the source type must be specified. For example,
25 in some embodiments, the user may only have to type in the file name for a delimited
26 ASCII file, or enter table name and passwords if a SQL database is the source. In other
27 embodiments, the user can visually parse records (including binary data) in the case of
28 fixed length ISAM or sequential files. Alternatively, the user can use a dictionary
29 browser to define the source record layout

30 The source type may be presented to the user in a list (*e.g.*, a drop-down or pull-
31 down menu). Further, in some embodiments, the source type may be automatically

determined by a file sniffer. A file sniffer is a pseudo-spoke object used to determine the file format of files where the file structure is unknown. It uses a set of rules for matching the file content to known file types. If the file type can be determined, the correct spoke object is automatically selected for the user.

The source type the user selects may require additional information to allow the transformation engine to connect, such as a server, User ID or Password. Preferably, spoke objects are implemented to work with a specific data format. The implementation may also include an interface used by the interface to determine what is required by the spoke for connecting to an instance of data. Thus, the spoke objects either contain all of the necessary parameter information or are operable to prompt the user to supply necessary parameters.

For example, the transformation engine may ask the user to define: the server, database directory, database name, user's identification and corresponding password, and/or source table. In some instances, a database may have several tables, and the user must select the table or tables from which the user wants to convert data.

In many cases, the present invention will be able to parse the data of known types of data sources correctly without additional user input. The present invention may be configured to automatically recognize the data structure and formatting or known types of data sources. For various reasons such as data corruption, the parsing may be incorrect. In other instances, the data source may not be of a known type. In both cases, the transformation engine may prompt the user for additional information to define the source. The type of information that is required depends on the types of data structures contained within the source, and of the type of source that is used. For example, the user may be prompted for source properties and source record layout information to define the data structures contained therein.

A source record layout contains information about the data structures in a particular data source. For example, it may contain information about the length of records and fields. The structure of commonly used sources may be predefined. With predefined files, it may be advantageous to prevent the user from making changes to the source record layout unless the user confirms that the data is not parsing correctly. In the case of a flat file or record manager file such as: fixed ASCII, binary, Btrieve, C-tree, C-

1 tree Plus, or COBOL, the user must define the structure of the source data file using one
2 of the following methods. The user may define the source record layout manually (see
3 below), or use an existing record layout.

4 *Ins All* If the source type is delimited ASCII, the present invention may present the user
5 with a hex browser to determine separators, delimiters and starting offset.
6 Advantageously, the user can use these values to for the source properties. The user can
7 also determine if there is a header record. A header record contains information, such as
8 column headings, but is not actual data. In addition, by scrolling through the data, the
9 user can view several records. After scrolling through the first few records, the user can
10 usually determine what the separators and delimiters are. Most field separators are
11 printable characters such as a comma (,) or a pipe (|). The user will see printable
12 characters in the single line of data. Some field and record separators are non-printable
13 characters such as a Carriage Return-Line Feed or a Tab. A non-printable character will
14 appear as a period (.) in the line of data, but in the line of hex values above the ruler, the
15 user will see the hex value of that character.

16 *Ins All* Flat, Fixed ASCII, Binary, and record manager data sources may not
17 automatically broken into records and/or fields because they do not contain delimiters or
18 separators to mark the locations of field and record breaks. The user must define how the
19 data will be broken up (also called parsed), using the source properties, source record
20 Layout, and source record Parser windows. One way of defining the data structures is
21 through the use of a parsing interface that allows the user to manually parse the data, *e.g.*,
22 by defining record length and starting offset, field sizes, field names, data types, and data
23 properties. Optionally, the parsing interface may include a data browser that parses
24 source data into the data structures defined by the user, allowing the user verify that the
25 structure is properly defined.

26 Next, the transformation engine connects to the specified source. Optionally, the
27 present invention may also display data from the source. Advantageously, the user can
28 use this display to verify that the transformation engine is parsing the source data
29 correctly.
30
31

Defining the target

Defining the target **410** is similar to defining the source **400**. The transformation engine must be provided with the information it needs regarding the target to which the data will be converted. In one embodiment, the user must specify the target type, name, and data types. In other embodiments, a default predefined data target may be used. In yet other embodiments, the target may automatically be defined to mirror the source.

In embodiments utilizing modal target adaptors, the present invention allows a great deal of flexibility in defining how data is written to the target by allowing the user to specify an output mode. In one embodiment, the output modes may be:

- **Replace File/Table** – create a new data target or table, OR overwrite both the data and the structure of an existing file or table
- **Append to File/Table** – keep the existing records and add new records to an existing file or table, OR add records to an empty table.
- **Update File/Table** – searches an existing data target for a match in the key fields, which the user defines in target keys/indexes, and updates data in the specified manner. May be particularly useful when the user has selected a dBASE, ODBC, or SQL target type.
- **Clear File/Table contents and Append** – preserves the target record layout and the relationships between tables (if the user has defined them) and discards any existing records. May be particularly useful if the user has selected an ODBC or SQL target type.
- **Delete from File/Table** – searches an existing data target for a match in the key fields, which the user has defines in target keys/indexes, and deletes data in the specified manner. May be particularly useful when the user has selected an ODBC, or SQL target type,

Optionally, during the transformation execution **500**, the contents of the data source may be displayed so that the user may can verify that the transformation is running properly.

Defining the Transformation Map

The user may define the transformation map **420** by specifying where the data from the source should appear in the data target as well as the relationship between

1 source data and target data. The transformation tells the transformation engine exactly
2 what to write to the target data file. The user can: match source field names to target
3 field names; associate source fields with target fields with different field names and in a
4 different order than they appear in the data source; parse (split) a field; concatenate
5 (merge) fields; perform mathematical calculations; remove unwanted characters; validate
6 date fields; and much more. Source fields that are not mapped to target fields may
7 generally be discarded when the transformation is executed. Alternatively, they may be
8 handled with the **reject** function (discussed below).

9 *Ans 11* In one embodiment, the user may use a visual mapping interface to drag and drop
10 and to match fields as the user likes (e.g. targetField = sourceField). However, any
11 technique for specifying that where source data should appear in the data target is within
12 the scope of the invention. Further, if the user wants to relate source and target fields, the
13 user can create numeric and logical expressions to massage data and fields into the exact
14 output format the user requires. Still further, the user can extract records that meet a
15 logical condition or fall into a range so that only a subset of the total records passing
16 through the transformation engine are written to the data target. In one embodiment, the
17 transformation system may default to a one-to-one mapping between source fields and
18 target fields unless the user specifies otherwise, as this is one of the most frequently used
19 mappings. However, any mapping may be used as the default without departing from the
20 scope of the invention.

21 Because, in some embodiments, the user can view source and target data at any
22 time in the process and test the results of any manipulations, the user won't waste time
23 executing incorrect transformations. In addition, because, in some embodiments, the user
24 can save the parameters governing a transformation, the user can easily apply the new
25 transformation specifications to future transformations.

26 The present invention contemplates the use of expressions when defining the
27 mapping between source and target data structures. Expressions allows users to modify
28 the data from its source format to the target format; select records meeting a certain
29 criteria for the data target (filtering); specify actions to be taken when an error occurs;
30 and perform many other functions. Further, if the user wants the result of one expression
31 to be used as a parameter or argument in another expression, the user may "nest"

expressions within expressions to produce the desired results. The only limit to the number of expression iterations that may be used is available system memory. In some embodiments, an expression builder interface may be included in the transformation engine to help the user write or generate expressions. The present invention is not limited to any particular programming language or syntax. Accordingly, the present invention is not limited to the syntax of the sample expressions, functions, etc.

When the user specifies an expression in the transformation map, the result of that expression is usually data that is written into the target data file. For example, the simplest expression sets a target field equal to a source field, *e.g.* Field1 = Fields("Field1"). This simple expression instructs the transformation engine to write the data from Field1 in the data source to Field1 in the data target.

In one embodiment, an expression may include any combination of the following elements:

Operands – values or text that the expression operates on. These could be an actual value, such as “4”, a field name, or any text string.

Operators – mathematical symbols, text characters or logical statements that tell the transformation engine what to do with the operands in an expression.

Numeric operators – perform calculations with values. Examples include +, -, *, /, and ^ for addition, subtraction, multiplication, division, and exponentiation, respectively. Numeric operators generally return a numeric value.

Logical operators – evaluate a condition. Logical operators include AND, OR and NOT. Logical operators join conditions. The conditions generally return true or false.

Comparison operators – compare two values to determine their relationship. Comparison operators include =, <, >, <=, >= and <> as well as LIKE, and ~ (contains) and !~ (does not contain). Comparison operators generally return true or false.

Separators – for combining various operations and nested expressions. The user may use parentheses (or some other indicator) in complex expressions to tell the transformation engine the order in which the user wants the expression

executed. Expressions inside parentheses are always executed first. For example, in the following expression –

GSub(Chr\$(034), "", [Fieldname])

– the Chr\$ function would be executed first.

Functions – for operations that require more complex, automated processing than the user interface can specify. Functions may use the syntax of existing programming languages or may use a syntax or language specific to a transformation system of the present invention. In one embodiment, a special built-in language may be used in expressions for several purposes including manipulating data, handling errors, and filtering records. The functions used in the transformation designer are similar to the functions in Visual Basic, but not identical. Examples of functions in the present disclosure use this language.

Statements – for operations that require more complex, automated processing than the user interface can specify. Similar to functions, statements may use the syntax of existing programming languages or may use a syntax or language specific to a transformation system of the present invention. In one embodiment, the statements use the same special built-in language described above, with the statements similar to, but not identical, to those in Visual Basic. Statements are usually associated with Flow Control and complex expressions.

Literal values (constants) – an exact value, alphabetic or numeric. Examples include, without limitation, 100 or "John Smith". Literal text may be enclosed in quotation marks (" ").

Special characters – allow the user to specify more complex and flexible conditions for matching character strings than simply "Is it the same string, or isn't it?" in an expression. Special characters may include: | (and) * + ? [and] - . \ ^ \$ { and }.

Arithmetic operators – used to perform arithmetical calculations on numeric data in a field or fields. They may be used alone or in combination with other operators and Functions in all sorts of expressions. Numeric operands may be

promoted to double precision values before performing the operation. If both operands are integer values and the result can be represented as an integer, then the operator will return an integer value. If one or both operands are Null, then the result is Null. All other values may be treated as a numeric value of zero.

+ add

- subtract

* multiply

/ divide two floating point operands

^ exponentiate

\ divide two integers

Generally, calculations cannot be performed on data that contains non-numeric characters, or is defined as text data type. However, functions may be available that allow the user to convert data from text to numeric values. Examples of functions that perform calculations follow:

- To add the contents of two or more source fields with source fields of "Total" and "Tax" and a target field of "Grand Total":

GRAND TOTAL = [Total] + [Tax]

- To multiply the contents of two fields from the data source with source field of "Quantity" and "Price" and a target field of "TOTAL SALE":

TOTAL SALE = [Quantity] * [Price]

- To multiply the contents of one field from the data source by a literal value (add 7.25% sales tax) with a source field of "Total" and a target field of "GRAND TOTAL":

GRAND TOTAL = [Total] * 1.0725

- To divide the contents of one field by the contents of another field from the data source with source fields of "Total" and "Quantity" and a target field of "Price Per":

PRICE PER = [Total Sale] / [Quantity]

It is noted that the preceding examples (along with all of the examples presented herein) are for illustrative purposes only and do not serve to limit the scope of the invention.

Logical operators may be used to specify multiple criteria in an expression. For example, logical operators may be used in extract logic when the user wants to select particular records based on information from two or more fields. Further, logical operators may also be used in target field expressions, in addition to countless other uses.

Three common logical operators include the **And** operator, the **Not** operator, and the **Or** operator. Examples of expressions with logical operators include, but are not limited to:

- To select only those records whose [Start Date] equals 01/01/94 **and** whose [End Date] equals 01/31/94 (within the same record) (the DateValue function may be used to convert text strings to dates):

```
[Start Date] = DateValue("01/01/94") And [End Date] =
DateValue("01/31/94")
```

- To select records when the [Start Date] and [End Date] fields are 'Text' or 'Character' data, enclose dates in quotation marks (here, the DateValue function is not necessary):

```
[Start Date] = "01/01/94" And [End Date] = "01/31/94"
```

- To select records where **either** the first **or** the second criteria is met. Select records whose [Start Date] field contains 01/01/94, regardless of the [End Date], and all records whose [End Date] field contains 01/31/94, regardless of the [Start Date]:

```
[Start Date] = DateValue("01/01/94") Or [End Date] =
DateValue("01/31/94")
```

- To select records where the [DateofBirth] field is not blank:

```
Not IsNull([DateofBirth])
```

Comparison operators may be used to compare the contents in a field to either the contents in another field or a constant. They may be used alone or in combination with other operators and functions in record filtering expressions, target field expressions, and other places where an expression is needed. With the exception of the contains (~) and does not contain (!~) operators, an entire field will be compared, and must match to return true. Contains and does not contain will return true if any part of the field matches the comparison value. These operators can also look for less specific patterns, rather than literal matches. Comparison operators include but are not limited to:

	Operator	Definition
1		
2	=	equal to
3	<>	not equal to
4	>=	greater than or equal to
5	<=	less than or equal to
6	<	less than
7	>	greater than
8	~	contains
9	!~	does not contain

10 Examples of expressions with comparison operators include:

11 To write this expression in source or target Filters:

- 12 • Select only the records in which the size field in the data source is exactly
13 "10mm":

14 [Size] = "10mm"

- 15 • Select only the records in which the quantity field in the data source is a
16 numeric value of **less than or equal to** 1000:

17 [Quantity] <= 1000

- 18 • Select only the records in which the quantity field in the data source is a
19 numeric value **greater than** 1000:

20 [Quantity] > 1000

- 21 • Select only the records in which the quantity field in the data source is a **Text**
22 field (e.g. an ASCII file) and must be **exactly 1000**.

23 Val[Quantity] = 1000

- 24 • Select only the records in which the ordered field in the data source contains
25 values **not equal to** the values in the shipped field

26 [Ordered] <> [Shipped]

- 27 • Select only the records in which the Address field contains "P.O.Box" with or
28 without capitol letters, periods, or spaces. This will convert all records for
29 people who have P. O. Box type addresses.

30 [Address] ~ "[Pp]\. * [Oo]\. * [Bb] [Oo] [Xx] "

- 31 • Select only the records in which the CityStateZip field does not contain a five
32 digit number. This will only convert records that are missing a zip code.

1 [CityStateZip] !~ "[0-9][0-9][0-9][0-9][0-9]"

2 A concatenation operator (e.g., "&") may be used to concatenate or merge data
3 from two or more fields in the data source into a single field in the data target. Examples
4 of expressions with the concatenation operator include:

- 5 • To concatenate two fields ("First Name" and "Last Name") from the data
6 source, with a space between the data in the data target:

7 [First Name] & " " & [Last Name]

- 8 • To concatenate three data source fields ("City", "State" and "Zip"), with a
9 comma and a space between two of the fields and two spaces between the
10 other two fields:

11 [City] & ", " & [State] & " " & [Zip]

12 A **Like** operator may be used to compare the value in a field with the value in
13 another field or a literal. It returns true if the value is found anywhere within the field. It
14 does not require an exact match. It also allows a pattern to be matched, not just a literal
15 value. It is very similar to the **contains** operator, but it uses different special characters,
16 and has different meanings for some of the same special characters. The **Like** operator
17 may perform a DOS-style comparison. The **Like** operator may be particularly useful
18 when the user is attempting to write record filtering expressions. For example, assume
19 that the user has a [State] field in the data source that is a 5 byte field and contains the
20 official two digit abbreviations for states in the United States. Further assume that the
21 user only wants to convert those records for the state of Montana (abbreviated MT).
22 Since the [State] field actually contains two letters and three spaces, the user should use
23 the **like** operator (instead of the = operator) so the transformation engine will look for the
24 letters "MT" anywhere within those 5 bytes of the field. In record Expression line of the
25 source Filters window, the expression would be written as follows:

26 [State] Like "MT"

27 A function generally returns a value based on the results of a calculation or other
28 operation. Common functions include, without limitation, **Date**, **Sub**, **Left**, and **Right**.
29 In one particular embodiment, the functions used in the transformation designer are very
30 similar to Visual Basic functions. The following is a non-exclusive listing of useful
31 functions used in one embodiment, grouped by category:

32 Format text fields

UCase - convert all letters to upper case

LCase - convert all letters to lower case

InitCaps - convert the initial letter in each word to upper case

Format - convert the data to a specified mask

Format date fields

DateValMask - specify that a source field is a date and its mask

DateConvert - convert one format of date to another

Parse (separate), rearrange, or clean information in fields

NamePart - parse or rearrange a name field

Add1Part - parse or rearrange a street address field

Add2Part - parse or rearrange a city-state-zip field

Add1Clean - clean street address fields to USPS standards

Parse - split any type of field at a particular character

Remove unwanted spaces from fields

Trim - remove leading and trailing spaces

LTrim - remove leading spaces

RTrim - remove trailing spaces

Search and replace characters in a field

Sub - substitute one string of characters for another (First occurrence within a field. Special characters can be used to replace patterns.)

GSub - substitute one string of characters for another (All occurrences within a field. Special characters can be used to replace patterns.)

StrReplace - substitute one string of characters for another (Special characters cannot be used. All characters will be treated as their literal values except quotation marks (" ")).

Transliterate - translates characters between two character sets

Use external lookup tables

Lookup - allows lookups on character strings using a simple 2-column table

TLookup - allows lookups on character strings using a multi-column table

Xlate - allows lookups on single characters, hex values, and decimal values

Manipulate data if it meets a condition

IIf - specify a condition, then a “true” action and a “false” action

Convert Data to a specific data type

CBool - change to a Boolean data type

CByte - change to a Byte data type

CDate - change to a Date data type

Cdbl - change to a Double data type

CInt - change to a Integer data type

CLng - change to a Long data type

CSng - change to a Single data type

Following is a list of additional functions that may be used with some embodiments of the present invention:

<u>Function</u>	<u>Description</u>
Abort	Causes a transformation to be aborted or stop running.
Abs	Returns the absolute value of a number.
Add1Fmt	Cleans (formats) street address fields to USPS standards.
Add1Part	Splits (parses) or rearranges a street address field and returns the parts, i.e., number, pre-directional, street name, suffix, post-directional, secondary address unit, and secondary address range.
Add2Part	Splits (parses) or rearranges an address field and returns the parts, i.e., city, state, and zip.
Asc	Returns the ASCII decimal code (not hexadecimal code) for the first character in a string.
CBool	Coerces a string into a Boolean data type.
CByte	Coerces a numeric string into a Byte data type.
CDate	Coerces a date string into a Date data type.
Cdbl	Coerces a numeric string into a Double data type.
CInt	Coerces a numeric string into an Integer data type.

1	CLng	Coerces a numeric string into a Long data type.
2	CSng	Coerces a numeric string into a Single data type.
3	Choose	Selects a value from a list of values.
4	Chr	Returns a one-character string from the ASCII character corresponding to an ANSI decimal code.
5		
6	Chr\$	Returns a one-character string from the ASCII character corresponding to an ANSI decimal code.
7		
8	Date	Return the current system date.
9	Date\$	Return the current system date.
10	DateAdd	Add or subtract a time interval to or from a date value.
11	DateConvert	Convert one format of date to another.
12	DateDiff	Determine the number of time intervals between two dates.
13	DatePart	Return a part of a date based on a specified time interval.
14	DateSerial	Construct a date value from specified year, month, and day values.
15		
16	DateValMask	Convert formatted date strings into real date values based on a date edit mask.
17		
18	DateValue	Convert a character string representation of a date into a date value.
19		
20	Day	Return the day of the month for a date value.
21	Eval	Evaluates a string expression and returns its value.
22	Exp	Returns <i>e</i> raised to a power.
23	Fix	Returns the integer portion of a number.
24	Format	Formats a number, date, time, or string according to instructions contained in a format expression.
25		
26	Format\$	Formats a number, date, time, or string according to instructions contained in a format expression.
27		
28	GSub (Replace All)	Globally replaces every instance of an expression string in one field of data with a specified string.
29		

1	Hour	Returns an integer between 0 and 23, inclusive, that represents the hour of the day corresponding to the time provided as an argument.
2		
3		
4	Iif	Returns one of two arguments, depending on the evaluation of an expression.
5		
6	InitCaps	Converts the first character of each word to uppercase.
7	InputBox	Displays a dialog box with a prompt, in which the user may input text or choose a button, and then returns the contents of the text box.
8		
9		
10	InputBox\$	Displays a dialog box with a prompt, in which the user may input text or choose a button, and then returns the contents of the text box.
11		
12		
13	InStr (Search)	Returns the position of the first occurrence of one string within another string.
14		
15	Int	Returns the integer portion of a number.
16	IsDate	Returns a value indicating whether or not another value can be converted to a date.
17		
18	IsNull	Returns a value that indicates whether or not another value contains the special Null character.
19		
20	IsNumeric	Returns a value indicating whether or not a value variable can be converted to a numeric data type. (-1) yes, (0) no.
21		
22	LCase	Returns a string in which all letters of an argument have been converted to lowercase.
23		
24	LCase\$	Returns a string in which all letters of an argument have been converted to lowercase.
25		
26	Left	Returns the leftmost n characters of a string argument.
27	Left\$	Returns the leftmost n characters of a string argument.
28	Len	Returns the number of characters in a string expression or the number of bytes required to store a variable.
29		
30	Log	Returns the natural logarithm of a number.
31	Log10	Returns the base 10 logarithm of a number.

1	LogMessage	Creates an entry in the Log File while a transformation is
2		running.
3	Lookup	Look for specific data in a field in the data source, and replace
4		that data in the data target with values from an external table.
5	LTrim	Returns a copy of a string with leading (leftmost) spaces
6		removed.
7	LTrim\$	Returns a copy of a string with leading (leftmost) spaces
8		removed.
9	Mid (Substring)	Returns a string that is part of some other string.
10	Mid\$	Returns a string that is part of some other string.
11	Minute	Returns an integer between 0 and 59, inclusive, that represents
12		the minute of the hour corresponding to the time provided as an
13		argument.
14	Month	Returns an integer between 1 and 12, inclusive, that represents
15		the month of the year for a date argument.
16	MsgBox	Displays a message in a dialog box and waits for the user to
17		choose a button, then returns a value indicating which button
18		the user has chosen.
19	NamePart	Splits (parses) a name field and returns the parts of a full name,
20		i.e., first, middle, last, either to the same field in a different
21		order or to a different field or fields.
22	Now (Timestamp)	Returns a date that represents the current date and time
23		according to the setting of the computer's system date and time.
24	Null	Used to insert a Null value in a field.
25	OptionExplicit	Requires variables be declared with Dim or Global before use.
26	OptionImplicit	Turns off the requirement that variables be declared with the
27		Dim or Global statement before use.
28	Parse (Unstring)	Splits (parses) a string of data in one field on a designated
29		character and returns the parts to a different field or fields.
30	Right	Returns the rightmost n characters of a string argument.
31	Right\$	Returns the rightmost n characters of a string argument.

1	Rnd	Returns a random number.
2	RTrim	Returns a copy of a string with trailing (rightmost) spaces removed.
3		
4	RTrim\$	Returns a copy of a string with trailing (rightmost) spaces removed.
5		
6	Second	Returns an integer between 0 and 59, inclusive, that represents the second of the minute for a time argument.
7		
8	Serial (Increment)	Returns the next serial value.
9	Sgn	Returns a value indicating the sign of a number.
10	Space	Return a string consisting of a specified number of spaces.
11	Space\$	Return a string consisting of a specified number of spaces.
12	Str	Return a string representation of the value of a numeric expression.
13		
14	Str\$	Return a string representation of the value of a numeric expression.
15		
16	StrComp (Compare)	Returns a value that indicates the result of the comparison of two string arguments.
17		
18	String	Return a string whose characters all have a given ANSI code or are all the first character of a string expression.
19		
20	String\$	Return a string whose characters all have a given ANSI code or are all the first character of a string expression.
21		
22	StrReplace	Replaces one literal string with another literal string.
23	Sub (Replace)	Replaces the first instance of an expression string in one field of data with a specified string.
24		
25	Switch	Evaluates a list of expressions and returns a value or an expression associated with the first expression in the list that is True.
26		
27		
28	TLookup	Allows lookups on character strings using a multi-column table.
29		
30	Time	Returns the current system time.
31	Time\$	Returns the current system time.

1	TimeSerial	Returns the time serial for a specific hour, minute, and second.
2	TimeValue	Returns the time represented by a string argument.
3	Transliterate	Translates characters between two character sets.
4	Trim	Returns a copy of a string with spaces removed.
5	Trim\$	Returns a copy of a string with spaces removed.
6	UCase	Returns a string in which all letters of an argument have been converted to uppercase.
7		
8	UCase\$	Returns a string in which all letters of an argument have been converted to uppercase.
9		
10	Val	Returns the numeric value of a string of characters.
11	ValMask	Returns a numeric value from a formatted string.
12	Weekday	Returns an integer between 1 (Sunday) and 7 (Saturday) that represents the day of the week for a date argument.
13		
14	Year	Returns an integer between 100 and 9999, inclusive, that represents the year of a date argument.
15		
16	XLate	Replaces one character value with another character value based on an external table. These can be specified in hex (x54), decimal (84) or character ('T') values.
17		

18
19 Further, in some embodiments, the user can use a decision structure to define
20 groups of statements that may or may not be executed, depending on the value of an
21 expression. In these embodiments the transformation engine may supports the following:
22 **For...Next, If...Then...Else, Select Case, While...Wend.** In addition the
23 transformation engine may also support the following error-trapping statements: **On**
24 **Error, Goto, Resume, Resume Next, Return.**

25 The user may use expressions to perform a variety of specialized data
26 manipulation or record filtering. For example, in one embodiment, with a single generic
27 ClearMapPut action, the transformation engine defaults to converting all records in the
28 data source to the data target. However, in this and other embodiments, the user may
29 specify one or more replacement or additional transformation filters. Typical uses for
30 transformation filters include, without limitation, converting records based on a
31 condition, converting a range of records, and converting a random sampling of records.

1 When a transformation is executed (described in detail in conjunction with **FIG. 5**), the
2 transformation engine may first filter records, and then perform target field expressions to
3 modify the actual data in a particular field. In another embodiment, the user can specify a
4 range on either the source side or the target side of the process. For example, if the user
5 wants the first 100 records from the source and then to extract a subset of those 100
6 records, the user would set a range in source sample and also set up the record filtering
7 expressions in the target. Conversely, if the user wants the transformation engine to read
8 all the records that meet the record filter expression criteria FIRST, then specify a range
9 of 100 of those records, the user would set the extract logic in the source Filter and the
10 Range in target Filter.

11 Some embodiments allow for records to be converted based on a condition. Here,
12 a user may use the expression language components to specify an expression that triggers
13 the condition. Generally, expressions written for filtering should be Boolean, with a true
14 return indicating that the record WILL be converted. For example, the following
15 expression - `Val([AccountBalance]) > "2000"` - will convert records where the
16 numerical value of the data in the AccountBalance source field is greater than 2000. If
17 this were the only transformation condition, other records would be discarded when the
18 transformation is run. Following are further examples of transformation conditions used
19 in one embodiment of the present invention:

<u>Source field</u>	<u>Objective and</u>
<u>Type</u>	<u>Sample Expression</u>
numeric	Convert records of customers whose balance falls within a certain range, <code>[BALANCE] >= "150.00" And [BALANCE] <= "2500.00"</code>
text	Convert records of customers whose balance falls within a certain range and interpret the field data as numeric instead of text, <code>Val([Balance]) >= "150.00" And Val([Balance]) <= "2500.00"</code>
date	Convert only records whose date falls within a specified range, <code>DateValue([DATE]) >= "01/01/94" And DateValue([DATE]) <= "12/31/94"</code>

1 date Convert records based on two or more date fields, where the user
2 only want records that contain a specific start and end date,
3 "19941215" in [Field1] and "19940915" in [Field2],
4 DateValMask([Field1] , "yyyymmdd") = "19941215" And
5 DateValMask([Field2] , "yyyymmdd") = "19940915"
6 text Convert records based on the date in a single field, where the user
7 only want records that contain dates between two dates,
8 "05/01/1994" and "05/05/1994", inclusive, in [Field1],
9 DateValue(Trim([Field1]))>=DateValue(Trim("05/01/1994
10 ")) And DateValue(Trim([Field1])) <= DateValue(Trim
11 ("05/05/1994"))
12 numeric Convert records based on the values in two fields, where the user
13 only want records where the contents of [Field1] are greater than
14 or equal to the contents of [Field2],
15 [Field1] >= [Field2]

16 In some embodiments, the user may use a **reject** function to create two files
17 during a transformation. One file may contain target data records and the other file may
18 contain source records that were rejected when the transformation was run. A record
19 may be rejected for several reasons including, without limitation, the record failing to
20 meet a filtering expression or function, and an error being detected while reading or
21 retrieving a record. Advantageously, the **reject** function may be helpful when debugging
22 a transformation and for noting data trends.

23 Other embodiments may include functionality for overflow handling. An
24 overflow occurs when numeric fields in the source have a higher precision than the target
25 numeric fields. The last few digits may be lost or the numeric value may be completely
26 altered. The user may specify rules to handle an overflow occurrence. For example, the
27 user choose to ignore the overflow, and the transformation will proceed as if the overflow
28 did not occur. The user may choose to treat an overflow occurrence as a warning, and the
29 transformation engine will display a warning message and/or write a message to a log file
30 indicating that an overflow has occurred, but the transformation will continue
31 uninterrupted. Alternatively, the user may choose treat overflow conditions as an error,
32 whereby the transformation engine will display an error message informing the user that

an overflow has occurred and if the maximum error count has been reached, the transformation will be aborted.

Yet other embodiments may include functionality to deal with truncation. Truncation occurs when the size of a target field is smaller than the size of the source field resulting in the last few characters of the source data being cut off. The user may specify the same handling as with the overflow functionality – ignoring, warning, and generating an error.

Optionally, a query language preprocessor may be included to express dynamic queries. For example, in one embodiment, the preprocessor processes a query statement by looking for markers in the SQL statement used to indicate an embedded expression. Each embedded expression is evaluated and the result of expression is substituted for the expression in the query. When all of the expressions have been substituted, the query is passed to the adaptor or spoke for execution.

For example the following SQL query contains an embedded expression referencing the 'Account No' field in the current source record:

```
delete from accounts where accountid = DJX(Fields("Account No"));
```

Assuming the value for 'Account No' is 123456, the preprocessor would translate the SQL query to:

```
delete from accounts where accountid = 123456;
```

The embedded expressions can be arbitrarily complex. Advantageously, the use of the preprocessor enables even more dynamic queries against the target.

Events

The event handling capabilities of the present invention allow tremendous flexibility in the handling of data. Different actions can be triggered at virtually any point in the transformation process. Messages can be logged, expressions can be executed, possible errors can be traced, normal data manipulation and memory clearing can be done, and the transformation itself can be ended or aborted. The user has complete control over when these actions occur, what actions occur, and how many actions occur. The user may specify a series of one or more trigger events and their associated actions, which is collectively referred to as an event action list. In some embodiments, a default

1 event action list may be used. In yet other embodiments, a previously stored event action
2 list may be used.

3 *Ins A22* Events are opportunities that can be exploited within the transformation cycle.
4 ~~Put another way,~~ they are moments in the timeline of the transformation. For example, if
5 the user wish something to happen as soon as a record is read into the transformation, the
6 user would choose the **AfterNextrecord** event, and then choose the action the user wish
7 to happen at that time.

8 *Ins A23* An advantage of the event handling in the present invention is that it provides for
9 far more complex transformations, e.g., with multiple record types on both source and
10 target, than prior art techniques. Further, the present invention allows these complex
11 transformations to be accomplished with very little difficulty. Examples of complex
12 transformations that may be performed by the present invention include, but are not
13 limited to, record aggregation, unrolling of data, transposing of data, and restructuring.
14 The event handling allows the user much of the flexibility, and customizability that the
15 user would get from a custom coded solution, without the hassle of building a custom
16 program every time the user wish to convert data.

17 *Ins A24* Events may generally be separated into four types: generic source events, generic
18 target events, transformation Events, and specific type events. The generic source and
19 target events are those that may be triggered during the reading and writing from all data
20 sources and data targets, respectively. In contrast, a specific type event is one that is
21 triggered with respect to a particular data source or target, or a specific type of data
22 structure. Transformation events are those that may be triggered during the actual
23 transformation process.

24 A sample non-exclusive list of events used in one embodiment of the present
25 invention is as follows:

- 26 • **BeforeTransformation** – triggered after transformation initialization and
27 before the start of the transformation loop. It may be useful to initialize global
28 variables used in mapping.
- 29 • **AfterTransformation** – triggered after the execution of a transformation. It
30 may be useful for freeing resources used in the transformation and for doing
31 other types of clean up.

- 1 • **BeforeNextRecord** – a generic source event that occurs just before the next
2 source record is read. It provides an opportunity to initialize variables used in
3 mapping.
- 4 • **AfterNextRecord** – occurs as both a generic source event and as a source
5 record type specific event. The generic event is fired after each source record
6 is read. The record specific version of the event is fired only when a record of
7 the specific type is read.
- 8 • **OnEOF** – a generic source event that occurs when the transformation engine
9 tries to read past the last record in the source file.
- 10 • **OnError** – a generic error event that may be triggered in cases where a more
11 specific error event occurs, but is unhandled (has no associated event actions).
12 It may also be triggered in cases where none of the more specific error events
13 are appropriate.
- 14 • **BeforeMap** – may occur as both a generic target event and as a record type
15 specific event, and is triggered just before mapping expressions are evaluated.
16 This event is sometimes used to filter out source records with missing or
17 invalid values.
- 18 • **AfterMap** – may occur as both a generic target event and as a record type
19 specific event, and is triggered after mapping expressions are evaluated. This
20 event is sometimes used to validate target values before they are sent to the
21 target.
- 22 • **BeforePutRecord** – may occur as both a generic target event and as a record
23 type specific event, and is triggered just before a target record is sent to the
24 target.
- 25 • **BeforePutRecord** – may occur as both a generic target event and as a record
26 type specific event, and is triggered just after a target record is sent to the
27 target. This event is sometimes used to reset accumulators.
- 28 • **OnAbort** – a generic target event that is triggered whenever the Abort()
29 function is called from an expression or when a user manually aborts or
30 cancels the transformation execution.

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28
- 29
- 30
- 31

- 1 • **OnDataChange5** – a source record type specific event that is fired whenever
- 2 a fifth data change monitor detects a change in a key value.
- 3 • **OnAllDataChange** – a source record type specific event that is triggered
- 4 whenever all data change monitors detect a change in a key value.
- 5 • **OnMismatch** – fired whenever a Delete Record or an Update Record fails to
- 6 match any records in the target object. This event is useful for situations
- 7 where it is desirable to modify a record if it exists and to add it if it does not.
- 8 In such cases the OnMismatch event handler would include an Insert Record
- 9 action to add the new record.

10 Event actions are actions that the user wishes to be executed at a specific moment
 11 or moments in the transformation. An event action's associated triggering event
 12 determines when the event action will be executed. Triggering events may be, but are not
 13 limited to, any of the events listed above. For example, if the user wishes a message to
 14 be placed in the error and event log every time a record is discarded, the user would
 15 choose the OnDiscard target event and the LogMessage action. Most actions can be
 16 triggered by any event that the transformation system is capable of detecting. A sample
 17 non-exclusive list of event actions used by one embodiment of the present invention is as
 18 follows:

- 19 • **Execute** – executes an expression that the user specify.
- 20 • **ClearMapPut** – combines the functionality of Clear, Map, and Put in one
- 21 action. The target record buffer is cleared, target field expressions are
- 22 executed, and the resulting data is written out to the data target.
- 23 • **MapPut** – executes target field expressions, assigns the resulting data to
- 24 target fields and writes the data to the data target, but does not clear the buffer.
- 25 If data from previous records is assigned to fields that do not exist in the most
- 26 recently read record, all of that data will be written along with the data from
- 27 the most recently read record.
- 28 • **Clear** – clears the contents of a target record memory buffer.
- 29 • **Map** – executes target field expressions and assigns the resulting data to target
- 30 fields in the memory buffer.
- 31 • **Put** – writes the data in the target record memory buffer into the data target.

- 1 • **Resume** – causes the transformation to continue normally after an error is
2 detected.
- 3 • **Terminate** – ends the transformation without aborting it. If the
4 transformation is transactional, it will not roll back, but will end normally. If
5 there is an action associated with an **AfterTransformation** event, it will be
6 executed.
- 7 • **Abort** – causes the transformation to abort. If the transformation is
8 transactional, the transaction will be rolled back. If there is an action
9 associated with the **AfterTransformation** event, it will not be executed.
- 10 • **LogMessage** – writes a message that the user specify to the error and event
11 log file.
- 12 • **LogTrgRec** – writes current target record buffer field values into the error and
13 event log file. This may be useful for diagnostic purposes.
- 14 • **TraceOn** – turns on error tracing so that details about each record
15 transformation will be written in the error and event log file.
- 16 • **TraceOff** – turns off error tracing and returns the logging to its normal state.

17 In one embodiment, when doing a standard one-record-type-to-one-record-type
18 transformation, the user may not need to specify any event actions at all. In this
19 embodiment, a **ClearMapPut** action may automatically be executed for the user when
20 the user runs the transformation. Any action or set of actions may be specified as the
21 default.

22 Generally, event actions may be processed in a predetermined order, which is
23 dependent on the triggering event. If multiple actions are associated with a single event
24 handler, the actions may be executed in the order in which they are defined. In some
25 embodiments, the user may modify the order of execution

26 In addition to being flexible, the event handling interface preferably designed to
27 be easy to use. The user chooses the event that the user wishes to have trigger an action,
28 and then choose the action and define its parameters. Screen interfaces may be used to
29 help the user define the parameters of each action as it is chosen. The user can choose to
30 have more than one action occur during a particular event, and the user can choose to
31 have the same action occur during more than one event. The present invention imparts

1 no restrictions on the number or type of event actions or triggering events that may be
2 used.

3 In addition, the transformation engine may allow users to create, save, and run
4 completed transformations, which contain all the information it needs to successfully
5 transfer data from one application to another application. It is common for users to have
6 a need to run the same transformation process on a repetitive basis.

Ins A27
8 Further, in some embodiments, either the user or the transformation engine may
9 generate metadata regarding a transformation. In these embodiments, this metadata may
10 be stored with the transformation and/or recorded in any logs that generated. One
11 example of metadata is the version information, which allows the user to specify portable
12 transformation specifications and their associated revision numbers. Thus, when the user
13 revises a transformation specification and want to make sure that its date and type are
14 traceable, the user can specify both major and minor transformation revisions. For
15 example a major revision may be numbered in whole numbers, e.g., 1, 2, 3, etc., and a
16 minor revision may numbered with decimals, e.g., 1.1, 1.2, etc. This information may
17 allow the user to keep designed transformations synchronized with transformations being
18 executed by the transformation engine.

18 EXECUTING THE TRANSFORMATION

19 The actual transformation process of the present invention is iterative. The
20 transformation engines retrieves a single piece of source data (e.g., a field, record, or
21 other data structure) at a time while detecting occurrence of triggering events until all of
22 the data sources have been retrieved. Advantageously, the transformation engine does
23 not have to load all of the source data structures into memory at once.

24 **FIG. 5** is a detailed flow chart that depicts execution of a transformation **500**
25 according to one embodiment of the present invention. Generally, after the necessary
26 transformation information has been specified (steps **400**, **410**, **420**, and **430**), the
27 transformation may be initiated **510**. The first step of the transformation is initialization
28 **600**. The flow chart in **FIG. 6** depicts the details of transformation initialization **600**
29 according to one embodiment of the present invention.

Ins A28
31 Once the transformation initialization is started **610**, it establishes connections
620 and **630** to transformation sources and transformation targets, respectively. The

embodiment shown in FIG. 6 makes use of a primary target and a reject target. Reject targets may be used to stored records that do not pass a filter or otherwise are not written to primary target. Reject targets are often useful in debugging and data analysis. Accordingly, the next inquiries 640 and 644 are whether both of the targets (i.e., the primary and reject) have record layouts specified for them. The illustrated embodiment is configured to use (642 and 646) the source layout for the targets, if none has been specified. In other embodiments, different default actions may be used, including, without limitation, requiring that the user select or specify a layout, and simply generating an error event. After establishing record layouts, the data targets are opened in preparation to receive output 650.

Next, the event handlers are initialized 660. Event handlers are used to detect and handle the occurrence of event actions and error events.

Returning to FIG. 5, after the initialize transformation routine 600 is completed, the system may log the transformation and start logging statistics 520. Though this step is optional, it may be useful in many cases for debugging purposes.

Next, a **BeforeTransformation** event may be fired 540 to allow for event actions before the transformation to take place. For purposes of the present invention, the term "fired" is synonymous with triggered. It is also noted, that the events depicted in this embodiment are merely illustrative and are not required – the present invention does not limit the types of events or actions that may be used.

Next, transformation loop 700 is entered. Transformation loop 700, described in more detail in FIG. 7, is one way that the transformation engine can iterate through the data sources. Record counters and error information are reset 712 at the start 710 of the loop. The loop continues until it determines that the transformation is finished 720.

In the loop, the presence of unhandled exceptions are checked 730. An unhandled exception is any error event for which there is not suitable event handler defined. These untrapped errors cause the transformation to terminate abnormally. If there is an unhandled exception, the transformation loop ends unsuccessfully.

If there are no unhandled exceptions, the system may fire a **BeforeNextRecord** event 740 and retrieves the next source record 750. By iterating through the data source(s) on a record-by-record basis, the whole data source does not have to be read into

1 memory. Further, this also allows for easy navigation of hierarchical data structures, as
2 the present invention can keep track of interrecord relationships between records. As the
3 transformation process of the present invention iterates over records from the data source,
4 the last instance of each distinct record type may be remembered. Thus, in instances
5 where data is either hierarchical or there is an implied parent-child relationship, mapping
6 expressions may address the data from any of the ancestors from the last record. Though
7 records are a commonly used, particularly with database sources, any size or type data
8 structure may be read in step 750.

9 **Inst A30** Next, if the end of the source file is detected 760, an EOF event may be 762. If
10 no other data source files remain then the transformation loop is ended 790, otherwise the
11 loop proceeds to step 730.

12 **Inst A31** If the end is not detected, retrieved source record 750 is checked for input error
13 764. If input error is detected, it is handled 766 by one or more error handlers. An error
14 handler is similar to an event handler in that it is designed to detect occurrence of an
15 event (*i.e.*, an error condition) and execute the appropriate action. The appropriate action
16 may be specified by the user or may be predefined. If the input error is handled then the
17 loop moves on to the same step (770) as if the input error did not occur. If the input error
18 is not handled 768, the transformation loop may be ended 790 unsuccessfully.

19 **Inst A32** If error handled successfully 768 or if there is no input error 764, data change are
20 evaluate monitors 770 to if any data monitors are triggered 772. This allows for
21 **OnAnyDataChange** events to be triggered 742. If all of the active data monitors
22 triggered, an **OnAllDataChange** event may be fired 744. If not, a sub-loop (780, 782,
23 and 788) may be executed that checks whether each individual the data monitor has been
24 triggered 784, and if so, fires the appropriate **OnDataChange** event 786. After the sub-
25 loop has executed, a record-layout-specific **AfterNextRecord** event 746 may be fired,
26 followed by a generic **AfterNextRecord** event 748.

27 After transformation loop 700 executes, an **AfterTransformation** event 544 may
28 be fired.

29 If the transformation was successful 550, the targets are closed 560, the
30 transformation end statistics may be logged 570, and the transformation is ended 580. If

TRANSFORMATION EXAMPLES

Included in this section are examples that illustrate the flexibility of the present invention. The syntax and formatting in the examples are not limitative as to the scope of the present invention.

The first example listed below depicts a simple mapping from a data source “SR1” to a data target “TR1” having the same data structures:

Source Layout SR1

PartNo NUMERIC(6)
Name TEXT(128)
Cost NUMERIC(9,2)

Target Layout TR1

TPartNo NUMERIC(6)
TName TEXT(128)
TCost NUMERIC(9,2)

TR1 Mapping Expressions

- TPartNo=Sources(0).Records("SR1").Fields("PartNo")
- TName=Sources(0).Records("SR1").Fields("Name")
- Tcost=Sources(0).Records("SR1").Fields("Cost")

SR1.AfterNextRecord Event Handler

- ClearMapPut("Target", "TR1")

After the transformation is executed (e.g., as described above with respect to FIG. 5), the source and data target would contain the following information:

SOURCE DATA

PartNo	Name	Cost
980123	CDRW	32.00
980522	MODEM	75.00
980331	MOUSE	26.00

DATA TARGET

TPartNo	TName	TCost
980123	CDRW	32.00
980522	MODEM	75.00
980331	MOUSE	26.00

The next example illustrates the use of a more complex mapping that incorporates functions:

Source Layout SR1

PartNo NUMERIC(6)
Name TEXT(128)
Cost NUMERIC(9,2)

Target Layout TR1

Items INTEGER
Total NUMERIC(9,2)

TR1 Mapping Expressions

- Items=Targets(0).Records("TR1").Fields("Items")+1
- Total=Targets(0).Records("TR1").Fields("Total")+
Sources(0).Records("SR1").Fields("Cost")

BeforeTransformation Event Handler

- Clear ("Target", "TR1")

SR1.AfterNextRecord Event Handler

- Map("Target", "TR1")

OnEOF Event Handler

- Put ("Target", "TR1")

After this transformation is executed, the data source and data target would contain the following information:

DATA SOURCE

DATA TARGET

PartNo	Name	Cost	Items	Total
980123	CDRW	32.00	3	133.00
980522	MODEM	75.00		
980331	MOUSE	26.00		

In this example, because of the nature of the function, data is only stored (*i.e.*, with the **PUT** action) once, after the entire data source has been read.

The next example illustrates the transformation of a source XML document to a target flat ASCII file. The XML data source in this example has three levels in the document tree. The header record (PO record) is formed by mapping values from the root level of the tree and from the BillingAddress sub-tree. The detail records are formed by mapping the Item sub-tree of the XML document.

XML DATA SOURCE

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<PurchaseOrder>
  <Data>2000/05/25</Date>
  <Billing Address>
    <Name>Fred's Computer Shop</Name>
    <Street>2901 Burnet Rd.</Street>
    <City>Austin</City>
    <State>TX</State>
    <Zip>78759</Zip>
  <Items>
    <Item>
      <Quantity>3</Quantity>
      <ProductNumber>980123</ProductNumber>
      <Description>Floppy Drive</Description>
```

```

1          <UnitCost>32.00</UnitCost>
2      </Item>
3      <Item>
4          <Quantity>1</Quantity>
5          <ProductNumber>980331</ProductNumber>
6          <Description>128M SDRAM</Description>
7          <UnitCost>129.00</UnitCost>
8      </Item>
9  </Items>
10 </PurchaseOrder>
11
12 Target Layout PURCHASE ORDER      Target Layout DETAIL
13 RecordType  TEXT(1)                  RecordType  TEXT(1)
14 Date        TEXT(10)                 PartNo      NUMERIC(6)
15 Name        TEXT(50)                 Name        TEXT(128)
16 Street      TEXT(50)                 Units       NUMERIC(6)
17 City        TEXT(25)                 Cost        NUMERIC(9,2)
18 State       TEXT(2)
19 Zip         TEXT(5)
20
21 PURCHASE ORDER Mapping Expressions
22
23 • RecordType="H"
24 • Date=Records("Date").Fields("Data")
25 • Name=Records("BillingAddress").Fields("Name")
26 • Street=Records("BillingAddress").Fields("Street")
27 • City= Records("BillingAddress").Fields("City")
28 • State= Records("BillingAddress").Fields("State")
29 • Zip=Left$( Records("BillingAddress").Fields("Zip"),5)\
30
31 DETAIL Mapping Expressions
32
33 • RecordType="D"
34 • PartNo=Records("Item").Fields("ProductNumber")
35 • Name=Records("Item").Fields("Name")
36 • Units= Records("Item").Fields("Quantity")
37 • Cost= Records("Item").Fields("UnitCost")
38
39 BillingAddress.AfterNextRecord event handler
40
41 • ClearMapPut ("Target","PO")
42
43 Item.AfterNextRecord event handler
44
45 • ClearMapPut ("Target","Detail")

```

After the transformation is executed, the data target would contain the following:

Fixed ASCII Data Target

H2000/05/25	Fred's Computer Shop	901 Burnet Rd.	Austin	TX78759
D980123	Floppy Drive		3	32.00
D9803311128M	SDRAM		1	129.00

This example illustrates that the present invention permits a hierarchical document to be restructured into a target with multiple record types. This is also an example of a many-to-many record type transformation.

Project Designer Interface

In other embodiments (not shown), the transformation engine may include a graphical "project" designer, allowing easy visual design and control of very complex end-to-end transformation Projects consisting of multiple steps. Sophisticated flow control enables the transformation engine steps (transformations) and non-steps to be assembled in a logical and dependent order for easy automation and deployment of batch executions. The project designer interface is a management tool for arranging the complete job of transforming data from one format to another. Users can use it to organize the transformation engine transformations with logical choices, SQL queries, global variables, Microsoft's DTS packages, and any other applications the user might need to complete the data transformation task. Once the user has organized these steps in the order of execution, then the user can execute, or even automate, the entire workflow sequence as one unit.

A transformation designer can be called from within the project designer interface, allowing for transformations to be created or edited in the transformation designer and the new information passed back to the appropriate transformation step in the project designer interface. All transformations needed for a project can be designed from within the project designer interface. Thus, the project designer interface can be used from beginning to end to make the data transformation task simpler and more streamlined.

Alternatively, template transformations can first be created and saved in the transformation designer. From within the project designer interface, those transformations can then be called and edited or overrides created and associated with individual steps in the project. These changes in the transformation can be saved in the

transformation engine database as part of the original transformation (edited), or the changed information can be passed back to the transformation step in the project designer interface without altering the original template transformation (overridden), at the user's discretion.

The first step in designing a transformation using the project designer interface is to consider what will be necessary to accomplish the complete job of transforming the data. It is useful for users to determine what needs to be done first, which applications will be needed, and what decisions will need to be made. When the user has a good sense of the strategy plan for transformation, the user should invoke the project designer interface. Project steps can be re-arranged, deleted, added, or edited as the user go along.

The general steps to design a project using the project designer interface are as follows: set the appropriate properties for a step – for example, if it is a transformation step, the user can invoke a transformation designer interface, create the transformation, edit the transformation, and set any overrides from a transformation properties menu; select another project step from the toolbar and click on the grid to place it and set the appropriate properties; repeating until all project steps have been set up; stepping through the execution; validating the project to make sure all of the essentials of a complete project are there; saving the project, if desired; and running the project, if desired.

The transformation engine includes a feature that allows users to combine multiple steps into a single complex transformation project. This feature is provided by the addition of a new visual project designer interface component and by enhancements to the existing transformation engine (the transformation engine) and transformation engine API (the transformation engine SDK) components.

The project designer interface provides an easy-to-use visual interface for the design, execution, and management of complex transformation projects. The user interface for the project designer interface includes both a project manager and a project design tool. In one embodiment, these tools may be configured to run on the Windows 95/98 and Windows NT operating systems.

The project manager allows the user to quickly see all of the projects in the transformation engine database. The manager uses an explorer-style interface to allow the user to navigate to the stored transformations and peruse some of the high-level

1 project content. The user is able to perform basic management operations on the
2 database contents (new, delete, edit, export, import, rename, etc.). Additionally, the user
3 is able to convert existing transformation batches into projects.

4 The project design tool represents the transformation projects using process flow
5 diagrams. The user may define a project using a simple diagramming interface. Each
6 step in the transformation project may be represented as symbols similar to those used in
7 flowcharts. The process flow is described using lines to connect the symbols for each of
8 the project steps. Transformation project diagrams will serve both to document the
9 project and to define how the project executes.

10 Transformation projects created through the project designer interface may
11 support several types of project steps:

- 12 • **Start.** This is a special step that represents the starting point for a
13 transformation project. It may also be used for the definition and initialization
14 of global project variables used to pass information between different project
15 steps.
- 16 • **Transformations.** Users may be able to create new transformation steps or
17 use existing transformation specifications. Transformation steps may be able
18 to share session information with other transformation steps to simplify the
19 specification of login information and to facilitate the coordination of
20 transactions across the entire project.
- 21 • **Decision.** The decision step provides a way for project to conditionally
22 control the project flow using an if-then-else logic. Decision steps supports
23 the use of simple expressions to test for branch conditions. Expressions may
24 have access to information stored, global variables, and completion code
25 information from prior steps to determine which branch of the process flow
26 continues execution.
- 27 • **Expression.** Expressions can be evaluated to compute values or to execute
28 functions from an external library. Expressions have access to global project
29 variables.

- 1 • **Application.** The application step allows users to incorporate the execution
- 2 of external applications such as schedulers, electronic mailers, sort utilities,
- 3 bulk loaders, and indexing utilities.
- 4 • **SQL Statement.** The SQL statement steps may provide an effective
- 5 mechanism for users to execute SQL DDL for the SQL resources used in a
- 6 project. Users may be able to define tables, indexes, primary keys, and
- 7 relational constraints. The combination of the SQL statement steps and the
- 8 transformation steps make it possible for the transformation engine to
- 9 populate entire databases at one time.
- 10 • **Sub-Project.** The use of sub-projects may allow smaller projects to be
- 11 combined into bigger projects and provides a mechanism for project reuse.
- 12 Sub-projects may also serve to give the user greater control over how
- 13 transactions are coordinated between multiple transactional steps.
- 14 • **Stop.** The stop step represents the end of a project. It can be used to specify
- 15 project termination expressions.

16 The transformation engine SDK may be enhanced to support new API functions

17 for the execution and management of projects and project steps. Following is a non-

18 exclusive list of preliminary API functions according to one embodiment of the present

19 invention:

- 20 • **LoadProject** Loads a Project from persistent storage files.
- 21 • **UnloadProject** Unloads the Project from memory.
- 22 • **ExecuteProject** Executes the Project
- 23 • **GetProjectName** Retrieves the Project Name
- 24 • **GetProjectAuthor** Retrieves the Project Author
- 25 • **GetProjectDate** Retrieves the Project Creation Date
- 26 • **GetProjectDescription** Retrieves the Project Description
- 27 • **GetProjectVersion** Retrieves the Project Version
- 28 • **GetProjectTransactionIndicator** Retrieves an indicator of whether the
- 29 Project is transactional or not.
- 30 • **Get/SetProjectLogFile** Accessors for the Project Log File path and filename.
- 31 • **Get/SetProjectLogMask** Accessors for the Project Log Mask.

- **Get/SetProjectPersistentStorageRootDirectory** Accessors for the Project Persistent Storage Root Directory property.
- **ValidateProject** Validates the Project.
- **AbortProject** Aborts Project execution.
- **GetProjectErrorCount** Retrieves the Error Count for the Project.
- **GetProjectLastErrorMessage** Retrieves the Last Message logged for the Project.
- **LogProjectMessage** Logs a message to the Project log file.
- **GetProjectSessionList** Retrieves a list of global Sessions defined on the Project.
- **GetProjectSessionCount** Retrieves the number of global Sessions defined on the Project.
- **GetProjectSession** Iterates over global Sessions returning the handle (name) one at a time.
- **SetProjectStepSession** Overrides the Session on a specified Step
- **GetProjectStepList** Retrieves a list of Project Steps.
- **GetProjectStepCount** Retrieves the number of Steps defined on the Project.
- **GetProjectStep** Iterates over the Project Steps returning the handle (name) one at a time.
- **Get/SetGlobalVariable** Accessors for Project global variable values.

Following is a non-exclusive list of step level API functions according to one embodiment of the present invention:

- **GetProjectStepName** Retrieves the Name of a Step.
- **GetProjectStepType** Retrieves the Type of a Step.
- **GetProjectStepDescription** Retrieves the Description of a Step.
- **GetProjectStepSession** Retrieves the Session of a Step.
- **Get/SetProjectSteptransformationName** Accessors for the transformation name on input transformation Step.

- 1 • **GetProjectStepAuthor** Retrieves the transformation author on input
2 transformation Step.
- 3 • **GetProjectStepDate** Retrieves the transformation Creation Date on input
4 transformation Step.
- 5 • **Get/SetProjectStepFile/Table** Accessors for the transformation File or
6 Table on input transformation Step and source or target indicator. Could also
7 use for SQL File on SQL Step.
- 8 • **Get/SetProjectStepQueryStatement** Accessors for the transformation
9 Query Statement on input transformation Step and source or target indicator.
10 Could also use for Query Statement on SQL Step.
- 11 • **GetProjectStepFilterCount** Retrieves the number of filters on an input
12 transformation Step and source or target indicator.
- 13 • **GetProjectStepFilter** Iterates over the filters returning one at a time on an
14 input transformation Step and source or target indicator.
- 15 • **GetProjectStepSampleType** Retrieves the sample type on an input
16 transformation Step and source or target indicator.
- 17 • **GetProjectStepSampleStart** Retrieves the sample start on an input
18 transformation Step and source or target indicator.
- 19 • **GetProjectStepSampleCount** Retrieves the sample count on an input
20 transformation Step and source or target indicator.
- 21 • **Get/SetProjectStepInitializationFile** Accessors for an initialization file
22 property on input Start Step.
- 23 • **Get/SetProjectStepTerminationFile** Accessors for a termination file
24 property on input Stop Step.
- 25 • **Get/SetProjectStepCommandLine** Accessors for the command line
26 property on input Application Step.
- 27 • **Get/SetProjectStepParameters** Accessors for the parameter list property on
28 input Application Step.
- 29 • **Get/SetProjectStepTimeoutIndicator** Accessors for the timeout indicator
30 on an input Application or SQL Step.

- **Get/SetProjectStepTimeoutSeconds** Accessors for the timeout seconds on an input Application or SQL Step.
- **Get/SetProjectStepExpression** Accessors for Expression for Decision and Expression Steps. Need list capabilities for Expression Step.

Data replication and synchronization

The problem of replication and synchronization is one of change management. Updates made on one data store need to be logged and propagated to each replicant. There are a variety of techniques for tracking changes including change data capture and transaction log mining. In all cases, the changes can be represented as a sequence of inserts, deletes, and modifications. Most data replication solutions are concerned with replication of data between like data stores. In a system where the replicants store data in different formats, using a transformation tool to transform the changed data to data manipulation operations on each replicant may be the best solution to the problem of heterogeneous replication.

Embodiments of the present invention address this problem by providing a mechanism for performing any sequence of data manipulation operations on one or more objects. In particular, the use of the event-driven framework and the mode-less adaptors makes this possible without the need for complex scripting or custom code.

Application Integration

Modern techniques for integrating disparate applications usually perform integration on an object level. In a typical business to business (B2B) scenario, two trading partners might exchange purchase orders and invoices as electronic documents. Each trading partner is likely to have a different backend accounting system. To facilitate the exchange of documents, it is necessary for each trading partner to agree on a common interchange format for the electronic documents. This makes it necessary for each of the partners to have a way to transform data to and from their accounting system to the interchange format.

In these types of situations, a transformation tool can be used to import and export the interchange format. Given that a document may represent data from many parts of the backend system, an effective transformation tool must be able to perform a variety of

1 data manipulation operations on several objects and do so in a transactional manner. For
2 many situations, it is also necessary to generate new unique identifiers for objects that are
3 imported into the backend system.

4 Embodiments of the present invention address this problem by providing a
5 mechanism for performing any sequence of data manipulation operations on one or more
6 objects. Additionally, in some embodiments of the present invention, individual objects
7 may be treated transactionally with the use of modeless adaptors.

8
9 The preceding examples are included to demonstrate specific embodiments of the
10 invention. It should be appreciated by those of skill in the art that the techniques
11 disclosed in the examples which follow represent techniques discovered by the inventor
12 to function well in the practice of the invention, and thus can be considered to constitute
13 preferred modes for its practice. However, it should be understood that the invention is
14 not intended to be limited to the particular forms disclosed. Rather, the different aspects
15 of the disclosed compositions and methods may be utilized in various combinations
16 and/or independently. Thus the invention is not limited to only those combinations
17 shown herein, but rather may include other combinations. Further, those of skill in the art
18 should, in light of the present disclosure, appreciate that many changes can be made in
19 the specific embodiments which are disclosed and still obtain a like or similar result
20 without departing from the spirit and scope of the invention.

REFERENCES

The following references, to the extent that they provide exemplary procedural or other details supplementary to those set forth herein, are specifically incorporated herein by reference:

Bernstein, Philip A. and Eric Newcomer, Principles of Transaction Processing (1997).

Goldfarb, C. F., The SGML Handbook (1990).

Linthicum, David S., Enterprise Application Integration (2000)

McGrath, S., Parseme, 1st: SGML for Software Developers (1998)

XSL Transformations (XSLT), Version 1.0, W3C Recommendation (16 November 1999) (URL, as of August 31, 2000, <http://www.w3.org/TR/1999/REC-xslt-19991116>)

000007 Austin 166063.1